

# **Hydrostatic Transmissions Fixed Displacement**

**Providing Customer-Driven Solutions** 

#### North American Hydraulics,

NAHI, LLC partnering with Brevini Fluid Power offering Hydrostatic Solutions for any Closed or Open Loop application.

#### **Features and Options:**

- 40 ° bent axis design
- Fixed displacement
- · Various control options
- Continuous working pressure to 6325 psi
- Max rpms up to 6960 rpm

### <u>Proven Solutions for the</u> <u>Following Applications:</u>

- Construction
- · Material handling
- Agricultural
- Utility Machines
- Forestry
- Off-Shore

Please contact NAHI for additional information on Brevini Directional Control Valves.

The above information should be used as a guide and is subject to change without notice.

Please contact NAHI for proper selection.



## **SH11C SAE Mount, Bent Axis, Fixed Displacement Motors**

Size	Displacement	Rated	Peak	Max Flow	Weight
	(in³)	(psi)	(rpm)	(gpm)	(lbs)
55	3.44	6325	6960	5000	42
63	3.84	6325	6960	5000	42
75	4.75	6325	6960	4500	53
90	5.49	6325	6960	4500	53
108	6.61	6325	6960	4000	78
125	7.62	6325	6960	4000	78
160/180	In Progress	In Progress	In Progress	In Progress	In Progress



