



NORTH AMERICAN HYDRAULICS

Hydrostatic Transmissions Variable Displacement

Providing Customer-Driven Solutions

North American Hydraulics, NAHI, LLC partnering with Brevini Fluid Power offering Hydrostatic Solutions for any Closed or Open Loop application.

Features and Options:

- 40 ° bent axis design
- Variable displacement
- Various control options
- Continuous working pressure to 6200 psi
- Max rpms up to 6900 rpm

Proven Solutions for the Following Applications:

- Construction
- Material handling
- Agricultural
- Utility Machines
- Forestry
- Off-Shore



SH7V SAE Mount, Bent Axis Variable Displacement Motors

Size	Displacement (in ³)	Rated (psi)	Peak (rpm)	Max Flow (gpm)	Weight (lbs)
55	3.72	6200	6900	71	62
75	4.91	6200	6900	85	79
108	6.86	6200	6900	100	104
160	9.81	6200	6900	132	139



Options and Controls:

- Hydraulic: 2 position and proportional control
- Electrical: 12 or 24 volt, 2 position and proportional control

Please contact NAHI for additional information on Brevini Directional Control Valves.

The above information should be used as a guide and is subject to change without notice. Please contact NAHI for proper selection.



NAHI, LLC – CUSTOMER SERVICE • 225-751-0500 • www.nahi.com

HTVD 041112